

Boomlift / Manlift

Used Boom Lift Nova Scotia - The boom lift is one of the most popular kinds of aerial machinery. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Workers need to remain safe as they access locations at higher altitudes. The material handling industry offers many boom lift models. Most boom lifts can be successfully run with a single operator. This equipment became popular in the orchard industry to harvest fruit without having to climb a ladder and balance heavy baskets or pails. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible Boom lifts can reach items even when it is impossible to move the machine right underneath the area you are working in, making it possible to fix overhead cables within telephone line and pole installation, window cleaning applications and similar circumstances. With a variety of joints allowing the machine to bend over or under items, the articulated boom lift is helpful for numerous applications. These sections can independently move to allow workers to gain access to a variety of places. Famous for their tight turning radius, articulated booms offer an ideal solution for narrow hallways and storage facilities. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. Articulated boom lifts are utilized commonly for working on overhead power lines and wires. Firefighters may use these machines and some articulated boom lifts have water cannons. Some models are built for extended reach applications and outfitted with telescoping sections. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. The nickname "spiders" has been given to these boom lifts due to their legs which can support the machine on rough or steep terrain. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Electric boom lifts are common for interior jobs due to their quieter options and lack of unhealthy carbon monoxide exhaust. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. No second operator is required as the platform operator can extend the lift with the controls. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. These machines are built to be stable and reliable. Some are able to extend to their full height capacity in less than 60 seconds. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Available in 4WD and the ability to fit through small spaces. Telescopic boom lifts are your best choice for combining reach and height. Jib The jib is the extension found at the end of the main boom and between the platform. Certain models offer an additional articulation point or hinge that allows the platform to travel horizontally and vertically. Jibs are an option on many telescoping and articulating boom lifts. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. The first articulating Genie Z-30/20 boom was launched in 1985. These machines became immediately popular with their up-and-over design that continues to make them sought after nowadays. Proper Safety Measures Safety is the utmost priority when operating any kind of boom lift. Safety hazards

must be advertised to everyone who is working in the area for best practices. Operating the equipment safely is vital for the operator and everyone in the vicinity. Before operating the machine, effective communication and essential safety gear need to be in place. Ensure there are no flammable or combustible items, open flame or lit cigarettes near the machine, engine fuels or battery gases. For the ultimate safety, it is important to have a visible, safely mounted and accessible fire extinguisher within the operators reach. It is important to maintain a clean work space around charging stations and work surfaces since clutter or tools could puncture tires or damage the machine or its components. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. Lifting and supportive devices need to stabilize the weight on hand. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Adequate ventilation and lighting are essential in garages, workshops and along workbenches. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report The boom lift components are divided and categorized to streamline the process of inspection. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. Programmed maintenance procedures are completed based on machine operating hours or during “pre-delivery” preparation. Set yourself up for success by consulting your maintenance manual before operating the equipment to ensure battery life, oil changes and fluid levels are ready to go.